



PRODUCT SPECIFICATIONS

ColorStar® Impressions Mats

SURFACE

Material: PET (polyethylene terephthalate) printed/disperse-dyed yarn - contains 50% post-consumer recycled plastic from drink bottles

Weight: 27 ounces/yard² **Construction:** Cut pile

Substrate: Freudenberg LUTRADUR® polyester spunbond non-woven fabric 3.8 oz. per square yard (130 grams per square meter)

BACKING (available with nitrile, SBR, or vinyl)

Material: Nitrile rubber - smooth, universal cleated or suction

Thickness Options:

Standard duty 52-mil (body thickness 52-mil; border thickness 94-mil)

Medium duty 65-mil (body thickness 65-mil; border thickness 107-mil)

Heavy duty 90-mil (body thickness 90-mil; border thickness 90-mil)

Material: SBR rubber (with 20% recycled content) - smooth or full cleated

Thickness: 48-mil (body thickness 48-mil; border thickness 90-mil)

Material: Vinyl (PVC) - smooth only

Thickness: 70-mil (body thickness 70-mil; border thickness 70-mil)

OVERALL MAT THICKNESS: 3/8 inch (0.375")

STANDARDS & TESTING

- Certified high-traction by the National Floor Safety Institute (NFSI)
- Passes flammability tests EN ISO 11925-2 (2010) and EN ISO 9239-1 (2010).
- Passes BS 4790 (1987) determination of the flammability of textile floor coverings.