



## PRODUCT SPECIFICATIONS

# Hog Heaven<sup>®</sup>

### **SURFACE**

Material: Nitrile rubber

### **CUSHION**

Material: High-density, closed-cell nitrile/PVC-blended foam

**OVERALL MAT THICKNESS:** 5/8 inch (0.6250" ) or 7/8 inch (0.8750") depending on the product selected

### **STANDARDS & TESTING**

- Durometer: 56
- Compression Deflection:
  - 5/8" Mat: 40% at 20 psi, 55% at 40 psi
  - 7/8" Mat: 47% at 20 psi, 64% at 40 psi
- Certified high-traction by the National Floor Safety Institute (NFSI)
- Passes flammability standard DOC-FF1-70
- Passes AATCC test method 134-1996
- ASTM C1028-96 static coefficient of friction:
  - Dry 0.92
  - Wet 0.86
- ESD rating of electrically conductive:
  - Surface to surface at 50% relative humidity  $2.6 \times 10^5$  ohms
  - Surface to surface at 12% relative humidity  $3.0 \times 10^5$  ohms
- ASTM D1667 water absorption: 0.01 pounds/foot<sup>2</sup> maximum
- ASTM D1056 temperature use: cold crack -20 degrees F
- Melt point over 500 degrees F; tested at temperatures up to 1800 degrees F for welding/slag resistance (results available upon request)